




PMB118T045SS-255A

20A/45V⁽¹⁾, low VF Planar MOS barrier diode

Mechanical Data

Chip Drawing	Item	Information	
	Die Size (A)	2998μm	118.0 mil
	Top Metal Pad Size (B)	2878μm	113.3mil
	Passivation seal (C)	/	/
	Wafer Thickness (D)	255 μm	10.0 mil
	Scribe Line Width (E)	80 μm	3.15 mil
	Wafer Size	6 inch	
	Top Side Metallization	PMB118T045SS-255A	Ag
	Back Side Metallization	Ti Ni Ag	
	Recommended Storage Environment	Stored in original container, in dry nitrogen, (6 months at an ambient temperature of 23°C±3°C)	

Electrical Characteristics (T_J=25°C, unless otherwise specified) ⁽²⁾

Parameter	Description	Min.	Typ.	Max.	Unit	Test Condition
V _{BR}	Reverse Breakdown Voltage	50	53	-	V	I _R =300μA
V _F	Instantaneous Forward Voltage	-	0.48	0.55	V	I _F =20A ⁽³⁾
I _R	Reverse Leakage Current	-	90	150		V _R =45V
T _J , T _{STG}	Operating and Storage Temperature	-40°C to 150°C Max				

Note:

(1) The preliminary wafer datasheet only for reference;

(2) This characteristics assumes the dies are assembled in TO-277 packages. Actual performance may degrade when assembled.

YJ does not guarantee device performance after assembly;

(3)